

## SERIES GSA SWD Power Supply

(Three Phase)

DIN RAIL MOUNT

COMPACT SIZE

UL 508 Approved



### FEATURES

Three phase input, DC low Voltage LED



### SPECIFICATIONS

Input Voltage	340 - 575 VAC
Frequency	47 - 63 Hz
Output voltage	Select: 24 VDC
Output voltage adj.	-7 / +20%
Min. Efficiency	89%
Temperature rating	-25°C to +71°C
Protection Type	Overload, Overvoltage, Over Temperature Protection, Input fuse
Safety Specification	EN60950
Connection	Screw Terminals

Selection Catalog Number	GSA SWD 305 D002705	GSA SWD 310 D002710	GSA SWD 320 D002720	GSA SWD 340 D002740
Output Voltage	24VDC	24VDC	24VDC	24VDC
Output Current	5 A	10 A	20 A	40 A
Approval	UL 508 Listed, CE	UL 508 Listed, CE	UL 508 Listed, CE	UL 508 Listed, CE
Mounting	Din Rail	Din Rail	Din Rail	Din Rail
List Each	\$165	\$215	\$320	\$575
Dimensions approx. mm (Inch)	H W D 123.6 74.3 112 (4.86") (2.93") (4.41")	H W D 123.6 88 110.7 (4.86") (3.50") (4.36")	H W D 123.6 150 111.3 (4.86") (5.91") (4.38")	H W D 126 275.7 112 (4.96") (10.85") (4.41")

