



**LOW COST  
WATER TIGHT  
DUST TIGHT**


All control stations below, as standard, are **Round Design**. If square is desired, simply place a "S" at the end of the part number.  
**Example:** B22-S4-101S (same list)

B22-S4-201-S \$63.00 List

### Start-Stop Non Metal PVC (UL 4X)


#### DESCRIPTION

**Type S4 Enclosures** are Non Metal PVC fully gasketed against dust and hose pressure water tight. (International Rating: IP 66 and UL 4X)

**Type S4X Enclosures** are UL and CSA - Fiberglass Reinforced Polyester and are fully gasketed & hose pressure water tight. 

**Type M4/12** are cast metal and meet NEMA 12/4 standards. Series B22mm Operators are Metal Nema 4/12.

#### ELECTRICAL RATINGS

All buttons supplied are heavy duty oil dust tight, Type 4(water tight) and Type 12/13. Each is 600 Volt, 10 Amp UL, CSA, 

Button Size: Part number example: B22S4-101	B22-S4 PVC		B22-S4X Polyester		B22-M 4/12 Cast Aluminum	
	B22-S4-	LIST	B22-S4X-	LIST	B22-M4/12	LIST
<b>ONE BUTTON</b>						
Start	-101	\$39.00	-101	\$106.00	-101	\$62.00
Stop	-102	39.00	-102	106.00	-102	62.00
Stop (Maintained Mushroom Button) (push pull)	-104	55.00	-104	122.00	-104	78.50
Stop (Maintained Mushroom Button) <b>per EN 418</b>	-114 -418	64.00	-114 -418	129.00	-114 -418	87.00
Stop (Momentary Mushroom Button)	-104MO	48.00	-104MO	113.00	-104MO	71.00
Jog	-105	39.00	-105	106.00	-105	62.00
<b>Off-On (Selector Switch)</b>	<b>-106</b>	<b>46.00</b>	<b>-106</b>	<b>112.00</b>	<b>-106</b>	<b>68.00</b>
Open-Close (Selector Switch)	-107	46.00	-107	112.00	-107	68.00
For-Rev. (Selector Switch)	-108	54.00	-108	119.00	-108	77.00
Hand-Off-Auto (Selector Switch)	-109	54.00	-109	119.00	-109	77.00
Man.-Auto (Selector Switch)	-110	54.00	-110	119.00	-110	77.00
<b>Red Pilot Light: Resistor Type 240V 60Hz</b>	-112	60.00	-112	127.00	-112	83.00
<b>Red Pilot Light: Full Voltage Type 120V AC or DC</b>	-113	44.00	-113	111.00	-113	67.00
<b>Enclosure Only with 7/8" Drilling</b>	<b>S4-405-M1</b>	<b>19.00</b>	<b>S4X-M1</b>	<b>86.00</b>	<b>BMD-G1</b>	<b>42.00</b>
<b>TWO BUTTON</b>						
Start-Stop	-201	66.00	-201	127.00	-201	84.00
On-Off	-202	66.00	-202	127.00	-202	84.00
For-Rev.	-203	66.00	-203	127.00	-203	84.00
<b>Up-Down</b>	<b>-204</b>	<b>66.00</b>	<b>-204</b>	<b>127.00</b>	<b>-204</b>	<b>84.00</b>
Open-Close	-205	66.00	-205	127.00	-205	84.00
High-Low	-206	66.00	-206	127.00	-206	84.00
<b>Red Pilot Light, 1 Button:</b>						
120V	-208	73.00	-208	130.00	-208	94.00
240V	-209	91.00	-209	148.00	-209	94.00
<b>Enclosure Only with 7/8" Drilling</b>	<b>S4-406-M2</b>	<b>27.00</b>	<b>S4X-M2</b>	<b>87.00</b>	<b>BMD-G2</b>	<b>47.00</b>
<b>THREE BUTTON</b>						
Start-Jog-Stop	-301	109.00	-301	153.00	-301	106.00
Open-Close-Stop	-302	109.00	-302	153.00	-302	106.00
Up-Down-Stop	-303	109.00	-303	153.00	-303	106.00
<b>For-Rev.-Stop</b>	<b>-304</b>	<b>109.00</b>	<b>-304</b>	<b>153.00</b>	<b>-304</b>	<b>106.00</b>
High-Low-Stop	-305	109.00	-305	153.00	-305	106.00
Up-Down-Run	-306	109.00	-306	153.00	-306	106.00
<b>Red Pilot Light and 2 Buttons:</b>						
(Start-Stop)	-307	112.00	-307	156.00	-307	112.00
120V AC or DC	-308	130.00	-308	174.00	-308	112.00
240V AC or DC	-308	130.00	-308	174.00	-308	112.00
<b>Enclosure Only with 7/8" Drilling</b>	<b>S4-408-M3</b>	<b>42.00</b>	<b>S4X-M3</b>	<b>93.00</b>	<b>BMD-G3</b>	<b>57.00</b>

**UL (4X) ENCLOSURES  IP 66 (FIELD PB MOUNTING) WEATHERPROOF AND HOSEPROOF**  
**Industrial enclosures** Junction Boxes/Pushbuttons Enclosures/ Terminal Boxes/Controls Enclosures

UL 4X

**ENCLOSURES ONLY** (22mm) 7/8" Standard Drilling or Optional (30mm) 1<sup>13/64"</sup>



S4-406-M2 Enclosure

# Holes xx	Scarlet S4 (PVC)			Fiberglass (4X)		Dimensions (Inches)				
	Cat. No.	List	H	W	D*	Catalog No.	List	H	W	D*
1	S4-405-M1	\$19.00	4.1	4.1	2.2					
1	S4-406-M1	26.00	4.9	3.2	2.6	B22-S4X-M1	\$86.00	7	4	3
2	S4-406-M2	27.00	4.9	3.2	2.6	B22-S4X-M2	87.00	7	4	3
3	S4-408-M3	42.00	6.9	4.1	3.2	B22-S4X-M3	93.00	9	4	3
4	S4-410-M4	43.00	6.9	5.9	3.2	B22-S4X-M4	94.00	9	4	3
6	S4-410-M6	45.00	6.9	5.9	3.2	B22-S4X-M6	98.00	6	6	4
8	S4-414-M8	66.00	8.7	6.9	4.7	B22-S4X-M8	108.00	10	8	4
12	S4-372-M12	110.00	11.1	8.7	4.3	B22-S4X-M12	112.00	10	8	4

\* Above enclosures are drilled for (22mm) 7/8" operators. For drillings to be (30mm) 1<sup>13/64"</sup> full size, change "M" to "S" in part number (same price). **Example: S4-405-S1 \$19.00 List**