


Mechanical Interlock


These interlocks are installed to prevent mechanically closing both breakers simultaneously.

Capable of three functions (also Padlockable provision)


Catalog No.	Frame	List Each
CBS-MI-1S	125A (15-125A)	\$195
CBS-MI-2S	250A (150-250A)	\$219
CBS-MI-4S	400A (300-400A)	\$230
CBS-MI-8S	800A (500-800A)	\$235



1. Left MCCB: ON/OFF is possible
Right MCCB: Off lock



2. Left MCCB: Off lock
Right MCCB: ON/OFF is possible



3. Both MCCBs are locked

1.



2.

3.

Fixed Locking Devices

Locking devices are designed for toggle type operators. This device allows the toggle to be locked in "Off" position for guaranteed isolation according to IEC 60947-2. OSHA lockout - tagout.

Catalog No.	Frame	List Each
CBS-FLD-1S	125A (15-125A)	\$58
CBS-FLD-2S	250A (150-250A)	\$62
CBS-FLD-4S	400A (300-400A)	\$98
CBS-FLD-8S	800A (500-800A)	\$102



Padlock dimensions


Padlock Provision

(Padlock not supplied)

Removeable Locking Devices

Removable lockout devices are useful in lockout/tagout requirements. Guaranteed lockout in "off" position a maximum of 3 field installed padlock devices.

Catalog No.	Frame	List Each
CBS-RLD-1S	125A (15-125A)	\$35
CBS-RLD-2S	250A (150-250A)	\$39
CBS-RLD-4S	400A (300-400A)	\$50
CBS-RLD-8S	800A (500-800A)	\$58



Padlock dimensions

Padlock Provision

(Padlock not supplied)