



# EMERGENCY DISCONNECTS MAIN DISCONNECTS



**SERIES D  
PADLOCKABLE OPEN TYPE**

**BASE MOUNT WITH  
SAFETY DOOR INTERLOCK**      **16 - 250A**

**600 VOLT      ON - OFF**

FRONT PANEL DRILLING D05 - 5  
BY-1 Operator 22MM Hole Mounting

**CE**



SIZE UNIT	RATED CURRENT		WITH BE OPERATOR		WITH D OPERATOR		
	I <sub>TH</sub> AMPS	UL/CSA GENERAL PURPOSE (INDUCTIVE) AMPS	CATALOG NUMBER (1 PADLOCK)	LIST PRICE	CATALOG NUMBER (3 PADLOCK)	LIST PRICE	
<b>3 POLE</b>  <b>8" Adjustable mounting depth as standard</b>	D05	16	16	E D05-3BE 1 SD-*	\$68	E D05-3D 3SD-*	\$75
	D1	25	25	E D1-3BE 1 SD-*	74	E D1-3D 3 SD-*	81
	D2	40	40	E D2-3BE 3 SD-*	106	E D2-3D 3 SD-*	113
	D3	63	63	E D3-3BE 3 SD-*	125	E D3-3D 3 SD-*	132
	DK4	80	80	E DK4-3BE 4 SD-*	167	E DK4-3D 4 SD-*	179
	D4	100	100	E D4-3BE 4 SD-*	184	E D4-3D 4 SD-*	196
	D5	125	125	E D5-3BE 4 SD-*	228	E D5-3D 4 SD-*	240
	D6	200	200	-	-	E D6-3D 5 SD-*	564
	D7	250	250	-	-	E D7-3D 5 SD-*	788

BY-1 Operator



**TYPE BY-1 OPERATOR HANDLE OPTION**

To order, add **BY** in place of **BE** in catalog number. **Add \$10 List.** Includes safety door interlock. Use on D05...D5 **DEFEATABLE OPERATOR**

**8" T DEPTH DIMENSION** is standard on units sized **16-250Amp** with through the door safety interlock mechanism.

**BY-1 ORDERED SEPARATELY \$35.00 List**

**IP 67 Rated.** Recommended for use on Type 1, 3R, 12, 4X Applications. TYPE BY-1 Operator with Safety Door Interlock can be bypassed by qualified technician for servicing.

**TO ORDER:**

**BY-1-\*SI** = For sizes D05, D1, D2, D3

**BY-1-\*S2** = For sizes DK4, D4 & D5

(Replace asterisk with color suffix)

Available in Black - SS and RG - Red/Yellow ONLY.

Ordering separately BY-1 includes patented misalign module, interlock key (for shaft) and bypass tool as standard.

Auxiliaries on page 193.

<b>4 POLE</b>  <b>8" Adjustable mounting depth as standard</b>	D05	16	16	E D05-4BE 1 SD-*	\$79	E D05-4D 3 SD-*	\$84
	D1	25	25	E D1-4BE 1 SD-*	84	E D1-4D 3 SD-*	89
	D2	40	40	E D2-4BE 3 SD-*	121	E D2-4D 3 SD-*	128
	D3	63	63	E D3-4BE 3 SD-*	140	E D3-4D 3 SD-*	147
	DK4	80	80	E DK4-4BE 4 SD-*	191	E DK4-4D 4 SD-*	196
	D4	100	100	E D4-4BE 4 SD-*	210	E D4-4D 4 SD-*	220
	D5	125	125	E D5-4BE 4 SD-*	245	E D5-4D 4 SD-*	260
	D6	200	200	-	-	E D6-4D 5 SD-*	640
	D7	250	250	-	-	E D7-4D 5 SD-*	870

\* **SUFFIX:** Add -RG for Red-Yellow operator handle.  
Add -SS for Black handle "D" type only.  
Add -SI for Black-Silver operator "BE" handle.

To substitute **NON-auto-alignment** safety door interlock for the auto-alignment style, change SD in part# to SDV.      **Deduct:** D1-(-\$6) list  
D2-(-\$14) list  
D3-(-\$20) list

**Catalog Number Code:**

"SD" -Safety Door (Interlock Design)

"BE" -1 padlock type

"D" -3 padlock type

"BY-1" -1 padlock type

-last digit in part number indicates faceplate size.

Part # example: E D1-3BE 1 SD-RG; SD = safety door interlock design, BE = 1 padlock type, 1 = size 1 face plate, RG = Red-Yellow handle.