



Type EEC

AC POWER CONTACTORS 3+4 POLE

100 Amp to 225 Amp Sizes



EEC 185

Three Pole Contactors List Price UL Approved	EEC 95- * \$ 195.00	EEC 115-+ * \$ 240.00	EEC 150- * \$ 290.00	EEC 185- * \$ 440.00
Four Pole Contactors List Price Not UL Approved		EEC115-4P - * \$ 460.00	EEC150-4P - * \$ 490.00	EEC185-4P - * \$ 520.00
Auxiliaries included with contactor	1 N.O.+ 1 N.C.	1 N.O.+ 1 N.C.	1 N.O.+ 1 N.C.	1 N.O.+ 1 N.C.
AC-1 Resistive Amps	125A	200A	250A	275A
AC-3 Motor FLA	95A	115A	150A	185A
Ⓢ General Purpose Amps	110A	175A	200A	200A
3 Phase Horse Power Voltage	HP	HP	HP	HP
	200 V	20	30	40
	230 V	25	40	50
	460 V	60	75	100
	600 V	60	100	125
Dimensions				
Height	mm	127	162	170
Height	Inches	5 "	6.38"	6.69 "
Width 3 / 4 pole	mm	84	164 / 200	164 / 200
Width 3 / 4 pole	Inches	3.35 "	6.46 / 7.87 "	6.46 / 7.87 "
Depth AC+DC Coil	mm	125	170	170
Depth AC+DC Coil	Inches	4.92"	6.69"	6.69"
(EEC 95 No DC Coil)				

Refer to page 14 for Coil VA data

*Coil Voltage Suffix

* - Add Suffix AC Voltage 50Hz + 60Hz	* - DC Voltage
-A 120V	-N 24VDC
-C 208V up to 220V	-O 48VDC
-E 480V	-P 125VDC
-F 600V (EEC 225 Max)	-R 220VDC
-D 380V	
-G 24V (EEC 330 Max)	
-H 277V	(EEC 95 No DC Coil)

Contact Factory for additional coil voltages not listed.

AUXILIARIES

1N.O. Aux + 1N.C. **included standard** (EEC 115 + larger contactors)

Additional auxiliaries (**8 MAX**) are possible. Refer to accessory page 30.

Part # Example : EEC 95 - A = 3 Pole 1 N.O. Aux + 1 N.C. Aux , 120 VAC Coil.

UL 508 SB Supplement (takes affect April 26 , 2006)
Type EEC 12 through 95

UL Approved suitable on a circuit capable of delivering not more than **100,000 RMS SYM. Amps** 480 Volts Max.

To Order "Box Lugs" See Page 28.
For Sizes EEC115 - EEC400.

- - 40° F Min. + 158° F Max
- 10,000,000 cycle Mechanical Life
- 1,000,000 cycle Electrical Life
- -15 % + 10 % Coil Voltage Range
- - Ring terminal capable