



Type EEC

AC POWER CONTACTORS 3 POLE

225 Amp to 500 Amp Sizes



EEC 265

Three Pole Contactors		EEC 225-*	EEC 265-*	EEC 330-*	EEC 400-*
List Price		\$ 580.00	\$ 610.00	\$ 786.00	\$890.00
Auxiliaries included with contactor		1 N.O.+ 1 N.C.	1 N.O.+ 1 N.C.	1 N.O.+ 1 N.C.	1 N.O.+ 1 N.C.
AC-1 Resistive Amps		315A	350A	400A	500A
AC-3 Motor FLA		225A	265A	330A	400A
cUL General Purpose Amps		250A	285A	360A	420A
3 Phase Horse Power Voltage		HP	HP	HP	HP
	200 V	55	60	75	100
	230 V	65	75	100	125
	460 V	135	150	200	250
	600 V	175	200	250	300
Dimensions					
Height	mm	197	203	206	206
Height	Inches	7.76"	7.99"	8.11"	8.11"
Width	mm	169	207	213	181
Width	Inches	6.65"	8.15"	8.39"	7.13"
Depth AC + DC Coil	mm	180	212	217	213
Depth AC + DC Coil	inches	7.09"	8.35"	8.54"	8.39"

Refer to page 12 for Coil VA data

*Coil Voltage Suffix

* - Add Suffix AC Voltage 50Hz + 60Hz	* - DC Voltage
-A 120V	-N 24VDC
-C 208V up to 220V	-O 48VDC
-E 480V	-P 125VDC
-F 600V (EEC 225 Max)	-R 220VDC
-D 380V	
-G 24V (EEC 330 Max)	
-H 277V	

Contact Factory for additional coil voltages not listed.

AUXILIARIES

1 N.O. Aux + 1N.C. **included standard** (EEC 225 + larger contactors)
 Additional auxiliaries (**8 MAX**) are possible. Refer to accessory page 30.

Part # Example : EEC 225 - A = 3 Pole 1 N.O. Aux + 1 N.C. Aux , 120 VAC Coil.

UL Approved suitable on a circuit capable of delivering not more than **100,000 RMS SYM. Amps** 480 Volts Max.

**To Order "Box Lugs" See Page 30
For Sizes EEC115 - EEC400.**

- - 40° F Min. + 158° F Max
- 10,000,000 cycle Mechanical Life
- 1,000,000 cycle Electrical Life
- -15 % + 10 % Coil Voltage Range
- - Ring terminal capable