

SERIES GSA SWD POWER SUPPLY (Single Phase) 5,12 & 48 VOLT DC OUTPUT

**DIN RAIL MOUNT
COMPACT SIZE
REGULATED OUTPUT**

5 & 10 Amp



FEATURES

Single phase input
Wide Input Range 100-240VAC




SPECIFICATIONS

Input Voltage	100 - 240 VAC
Frequency	47 - 63 Hz
Output voltage	Select: 5VDC, 12VDC, 48VDC
Temperature rating	-10° + 50°C
Approvals	02-UL1950, UL508 listed, Class 2, 05, 10, 20 - UL 508 Listed
Protection Type	Internal Fuse T2A / 250 VAC
Connection	02-Quick Connect Terminals, 05,10 ,20 -Screw Clamp Terminals

Selection	GSA SWD 02/5			GSA SWD 02/12			GSA SWD 5/12			GSA SWD 10/48			GSA SWD 20/48		
Catalog Number	D 0023 50			D 0023 51			D 0023 06			D 0023 18			D 0023 28		
List Each	\$80.00			\$80.00			\$120.00			\$180.00			\$300.00		
Output Voltage	5VDC			12VDC			12VDC			48VDC			48VDC		
Output Current	10 A			5A			10A			5A			10A		
Noise in mV	50			50			100			100			100		
Dimensions approx. mm (Inch)	H	W	D	H	W	D	H	W	D	H	W	D	H	W	D
	90 (3.5")	40 (1.6")	115 (4.5")	125 (4.9")	63 (2.5")	126 (5.0")	125 (4.9")	83 (3.3")	126 (5.0")	125 (4.9")	175 (6.9")	116 (4.6")			



**Din Rail Mount
SWD**



**Dimensions
Approx.**

Discount Schedule: DE