



Type ECX - Special Purpose Contactor 3 & 4 Pole Contactors



Three Pole	Part #	ECX 18- *	ECX 32- *	ECX 65- *	ECX 95- *
Three Pole	List Price	\$ 28.00	\$ 42.00	\$ 80.00	\$ 126.00
Built in Auxiliaries		1N.O.	1N.O.	1N.O + 1 N.C..	1N.O + 1 N.C..
Resistive Amps AC-1 , 660V		32A	50A	80A	110A
240 Volts Motor Full Load Amps		22A	32A	68A	80A
3 Phase Horse Power Voltage:		HP	HP	HP	HP
200V		7 1/2	10	20	30
240V		7 1/2	15	25	30
460V		10	20	40	50
600V		10	20	40	50
IEC AC-3 380V Amps		18	32	65	95
IEC AC-3 660V Amps		12	21	42	49
Single Phase UL ratings					
115V 1 Phase HP		1	3	5	7 1/2
230V 1 Phase HP		3	5	15	20
Dimensions - 3 Pole		ECX 18	ECX 32	ECX 65	ECX 95
Height	Inches	3"	3.4"	5.08"	5.08"
Width	Inches	1.85"	2.24"	3"	3.43"
Depth	Inches	3.43"	3.94"	4.6"	5"
Depth with Extra Snap On Auxiliary					
	Inches	4.75"	6.08"	6.08"	6.50"
AC Coil Power	3 + 4 Pole	ECX 18	ECX 32	ECX 65	ECX 95
Holding VA		8	11	20	20
Pick Up VA		70	110	200	200

Four Pole Part #	ECX254N.O.-	Dimensions
List Price	\$ 40.00	H = 86mm
40 Amp Resistive, : FLA28 @ 240V		W = 57mm
200V-7.5HP / 240V -10HP / 480V-15 HP		D = 97mm

Four Pole	
Part #	Part #
ECX654N.O.-	ECX954N.O.-
\$ 88.00	\$ 130.00
77 mm wide	95 mm wide

* Coil Voltage Suffix	
* Add Suffix to Part #/AC Voltage 60 Hz	
- A	120V
- C	208 / 230V
- E	480V
- F	600V
- G	24V
* Add Suffix letter to part # Part # Example : ECX 18-A = 120 VAC Coil	

- DIN Rail Mountable
- Screw mount option
- Metal Base ECX 65 & ECX 95
- 600,000 Electrical Operations Life
- 6,000,000 Mechanical operations life
- Tolerance short circuit 5KA RMS SYM., 600V Max
- ECX18 & ECX32 available with 1N.C. Add ".01" to part#
Part # Example ECX18.01-*
- Six Auxiliaries Max (4 Max ECX 18, 32)
- 4°F + 122°F temperature
- 22 % + 10 % Coil Voltage (-22% does not apply to 208V)
- Ring terminal Capable.