



Type RTECX 3 Phase Reversing Motor Starters

AC-1	AC-3(@380V)	Horse Power Ratings 3 Phase Motor		OPEN	NEMA 1 General Purpose (metal)	NEMA4X Hose Dust Tight (non metal)	NEMA 4/12 (metal)	NEMA 3R Hose + Dust Tight Outdoor (metal)
		Volts	HP					
32A	18A	200V	7 1/2	RTECX 18 - * 0 - ⊕ \$110.00	RTECX 18 - * 1 - ⊕ \$203.00	RTECX 18 - * 4X - ⊕ \$223.00	RTECX 18 - * 4 - ⊕ \$263.00	RTECX 18 - * 3R - ⊕ \$263.00
		230V	7 1/2					
		480V	10					
		600V	10					
		Volts	HP					
50A	32A	200V	10	RTECX 32 - * 0 - ⊕ \$143.00	RTECX 32 - * 1 - ⊕ \$221.00	RTECX 32 - * 4X - ⊕ \$245.00	RTECX 32 - * 4 - ⊕ \$281.00	RTECX 32 - * 3R - ⊕ \$249.00
		230V	15					
		480V	20					
		600V	20					
		Volts	HP					
80A	65A	200V	20	RTECX 65 - * 0 - ⊕ \$261.00	RTECX 65 - * 1 - ⊕ \$326.00	RTECX 65 - * 4X - ⊕ \$347.00	RTECX 65 - * 4 - ⊕ \$407.00	RTECX 65 - * 3R - ⊕ \$379.00
		230V	25					
		480V	40					
		600V	40					
		Volts	HP					
110A	95A	200V	30	RTECX 95 - * 0 - ⊕ \$401.00	RTECX 95 - * 1 - ⊕ \$511.00	RTECX 95 - * 4X - ⊕ \$547.00	RTECX 95 - * 4 - ⊕ \$549.00	RTECX 95 - * 3R - ⊕ \$515.00
		230V	30					
		480V	50					
		600V	50					
		Volts	HP					

Pushbuttons and Transformers for starters see Accessories page

All above Reversing starters come standard with 2N.O. + 2N.C. Aux contacts.

*Coil Voltage Suffix		
* - Add Suffix	AC Voltage	
-A	=	120V
-C	=	230V/208V
-E	=	480V
-F	=	600V
-D	=	380V
-G	=	24V
-H	=	280V

PART # EXAMPLE :

RTECX 18 - A1-10A

RTECX = ECX 18 Reversing Contactor

A = 120 VAC Coil

1 = NEMA 1 Enclosure

10A = 7-10 AMP Overload

⊕ Add to Part #	Overload Amp Range
.63A	-.4 - .63A
-1A	-.63 - 1A
1.6A	-1 - 1.6A
-2A	-1.25 - 2A
-2.5	-1.6 - 2.5A
-4A	-2.5 - 4A
-6A	-4 - 6A
-8A	-5.5 - 8A
-10A	-7 - 10A
-13A	-9 - 13A
-18A	-12 - 18A
-25A	-17 - 25A
-32A	-23 - 32A
-36A	-28 - 36A
-40A	-30 - 40A
-50A	-37 - 50A
-65A	-48 - 65A
-80A	-63 - 80A
-93A	-80 - 93A

Dimensions for RTECX Starters

mm/inches	H	x W	x D
RTECX 18	118 (4.65")	105 (4.13")	125 (4.92")
RTECX 32	140 (5.51")	127 (5.00")	138 (5.43")
RTECX 65	180 (7.09")	165 (6.50")	154 (6.06")
RTECX 95	180 (7.09")	172 (6.77")	165 (6.50")

