



TYPE XLSK AC STARTERS

3 Phase Full Voltage-Across the Line



All Starters Supplied with BUILT-IN HEATERS Size 3-5

NEMA RATED

AC-1	AC-3	Horse Power Ratings 3 Phase Motor Max UL Volts HP		OPEN	ENCLOSED					NEMA HP
					NEMA 1 General Purpose (metal)	NEMA 4X Outdoor Dust Tight (non metal)	NEMA 4 (metal)	NEMA3R Rain Tight (metal)	NEMA12 Dust Tight (metal)	
140	95	200V 25 HP	30 HP	XLS45K	XLS45K	XLS45K	XLS45K	XLS45K	XLS45K	
		230V 30 HP	40 HP	-*0-***	-*1-***	-*4x-***	-*4-***	-*3R-***	-*12-***	
		460V 60 HP	75 HP	\$535	\$638	\$735	\$994	\$708	\$708	
		600V 75 HP		LIST						
140	105	200V 30 HP	40 HP	XLS55K	XLS55K	XLS55K	XLS55K	XLS55K	XLS55K	200V 25 HP 230V 30 HP 460V 50 HP 600V 50 HP NEMA 3
		230V 40 HP	75 HP	-*0-***	-*1-***	-*4x-***	-*4-***	-*3R-***	-*12-***	
		460V 75 HP	75 HP	\$625	\$777	\$1,302	\$1,532	\$1,332	\$1,332	
		600V 75 HP		LIST						
250	150	200V 40 HP	50 HP	XLS75K	XLS75K	XLS75K	XLS75K	XLS75K	XLS75K	
		230V 50 HP	100 HP	-*0-***	-*1-***	-*4x-***	-*4-***	-*3R-***	-*12-***	
		460V 100 HP	125 HP	\$1,020	\$1,330	\$1,720	\$1,840	\$1,840	\$1,840	
		600V 125 HP		LIST						
250	185	200V 50 HP	60 HP	XLS90K	XLS90K	XLS90K	XLS90K	XLS90K	XLS90K	200V 40 HP 230V 50 HP 460V 100 HP 600V 100 HP NEMA 4
		230V 60 HP	125 HP	-*0-***	-*1-***	-*4x-***	-*4-***	-*3R-***	-*12-***	
		460V 125 HP	150 HP	\$1,270	\$1,580	\$1,970	\$2,308	\$2,072	\$2,072	
		600V 150 HP		LIST						
315	205	200V 60 HP	75 HP	XLS110K	XLS110K	XLS110K	XLS110K	XLS110K	XLS110K	
		230V 75 HP	150 HP	-*0-***	-*1-***	-*4x-***	-*4-***	-*3R-***	-*12-***	
		460V 150 HP	150 HP	\$1,550	\$2,275	\$3,250	\$2,777	\$2,404	\$2,404	
		600V 150 HP		LIST						
315	250	200V 60 HP	75 HP	XLS132K	XLS132K	XLS132K	XLS132K	XLS132K	XLS132K	
		230V 75 HP	150 HP	-*0-***	-*1-***	-*4x-***	-*4-***	-*3R-***	-*12-***	
		460V 150 HP	150 HP	\$1,660	\$2,385	\$3,360	\$2,928	\$2,555	\$2,555	
		600V 150 HP		LIST						
450	309	200V 100 HP	100 HP	XLS160K	XLS160K	XLS160K	XLS160K	XLS160K	XLS160K	200V 75 HP 230V 100 HP 460V 200 HP 600V 200 HP NEMA 5
		230V 100 HP	250 HP	-*0-***	-*1-***	-*4x-***	-*4-***	-*3R-***	-*12-***	
		460V 250 HP	300 HP	\$1,860	\$2,585	\$3,560	\$3,079	\$2,706	\$2,706	
		600V 300 HP		LIST						
600	420	200V 125 HP	150 HP	XLS220K	XLS220K	XLS220K	XLS220K	XLS220K	XLS220K	
		230V 150 HP	300 HP	-*0-***	-*1-***	-*4x-***	-*4-***	-*3R-***	-*12-***	
		460V 300 HP	400 HP	\$2,323	\$3,623	\$4,023	\$5,848	\$4,080	\$4,080	
		600V 400 HP		LIST						
700	550	200V 150 HP	200 HP	XLS280K	XLS280K	XLS280K	XLS280K	XLS280K	XLS280K	
		230V 200 HP	400 HP	-*0-***	-*1-***	-*4x-***	-*4-***	-*3R-***	-*12-***	
		460V 400 HP	500 HP	\$3,310	\$4,750	\$5,010	\$8,926	\$5,270	\$5,270	
		600V 500 HP		LIST						

For LS4K-LS18K (3 pole)		
AC	60Hz	50Hz
-G	24	24
-A	120	120
-B	200	200
-C	220	220
-H	277	230
-E	480	380
-F	600	500
DC add \$30 to list		
-MSW	12 VDC	
-NSW	24VDC	
-OSW	48 VDC	
-PSW	110 VDC	
-RSW	220 VDC	

For LS22K-LS55K (3 pole)		
AC	60Hz	50Hz
-G	24	24
-A	120	120
-B	200	200
-C	220	220
-H	277	230
-E	480	380
-F	600	500
DC add \$40 to list		
-NSW	24-28 VDC	
-OSW	42-48 VDC	
-PSW	110-127 VDC	
-RSW	220-250 VDC	

For LS75K-LS375K (3 Pole)	
AC/DC	50/60 Hz + DC
-N	24-28V
-AP	110-127V
-CR	220-250V
-EX	440-500V

* Coil Suffix

No Addition for DC above.

Part # Example: XLS45K:
XLS45K= Size LS45K Contactor
A= 120 VAC Coil
I= NEMA 1 Enclosure
Q= 30-40 Amps

** Overload Relay Suffix			
O.L. Relay Setting Range		O.L. Relay Setting Range	
Suffix	(Amps)	Suffix	(Amps)
-B	0.16-0.26	-ON	21-26
-C	0.25-0.41	-P	25-32
-D	0.4-0.65	-Q	30-47
-E	0.65-1.1	-QN	42-55
-F	1.1-1.5	-RN	54-65
-G	1.3-1.9	-SN	64-82
-H	1.8-2.7	-TM	78-97
-I	2.5-4	-TN	90-110
-K	4-6.3	-TT	110-140
-L	5.5-8.5	-U	140-190
-M	8-12	-V	175-280
-N	10-16	-W	200-310
-O	14.5-18	-WT	250-400
-OM	17.5-22	-X	315-500