

TYPE LS-K 4-POLE AC CONTACTORS

4 N.O POWER POLES (CODE - 4) 2 N.O. & 2 N.C. POWER POLES (CODE - 22)					600 VOLT AC CE					
Max Horsepower				AMPS (600V)		Part Number	List Price	DIMENSIONS (mm) without aux. contacts		
(3 Phase) Voltage				AC-1	UL/CSA Inductive			W	H	D [^]
200	230	460	600							
3	3	7.5	10	25	25	LS5K-4-*	\$92.00	81	45	85/115
						LS5K-22-*	92.00	81	45	85/115
5	5	10	15	32	32	LS7K-4-*	94.00	81	45	85/115
						LS7K-22-*	100.00	81	45	85/115
5	7.5	15	15	45	32	LS11K-4-*	120.00	87	55	98/134
						LS11K-22-*	120.00	87	55	98/134
10	10	20	25	60	54	LS15K-4-*	215.00	87	55	98/134
						LS15K-22-*	215.00	87	55	98/134
10	10	25	25	90	55	LS18K-4-*	260.00	118	87	119/147
						LS18K-22-*	260.00	118	87	119/147
20	20	50	50	110	100	LS30K-4-*	350.00	118	87	119/147
						LS30K-22-*	350.00	118	87	119/147
20	25	50	60	110	100	LS37K-22-*	398.00	118	87	119/147
25	30	60	75	140	140	LS45K-4-*	440.00	118	96	126/154
30	40	75	75	200	140	LS55K-4-*	627.00	200	150	176
50	60	125	125	325	156	LS90K-4-*	1,200.00	225	210	246
60	75	150	150	400	200	LS132K-4-*	1,745.00	225	210	246
100	100	200	300	500	310	LS160K-4-*	2,300.00	225	210	246
125	150	300	400	600	500	LS220K-4-*	2,800.00	218	214	228
150	200	400	500	700	650	LS280K-4-*	3,950.00	218	214	228
200	250	500	600	1000	810	LS375K-4-*	5,400.00	250	269	304
350	450	900	900	1250	1215	LS450K-4-*	9,450.00	380	558	327

NOTE: Above contactors, LS5K - LS55K are supplied without auxiliaries.

* **COIL SUFFIX** - Select coil from chart on the previous page.

For accessories - see page 65, 68.

▲ AC Depth/DC Depth



LS37K-22-A
4 pole (2 N.O. / 2 N.C., 100 Amp.)



LS450K-4. 11-A
4 pole (N.O., 1250 Amp.)

Standard Auxiliary Contacts (4-Pole Contactors)	
Contactors	Standard Auxiliary
LS4K - LS55K	Without Auxiliary
LS90K - LS450K	1N.O., 1 N.C.

Accessories on page 66.