



## ADDITIONS AND SPECIAL FEATURES MAGNETIC STARTERS AND CONTACTORS

### Factory Installed Suffixes & Lists

	Additions or Special Features	Enclosure Type	Catalog Suffix Number	EEC	EEC	EEC	EEC	EEC	EEC	EEC	EEC	EEC
				12 → 32	40 → 65	80 → 95	115 → 150	185 → 225	265 → 330	400 → 500	630	780
				LS4K LS5K LS7K	LS11K	LS18K	LS22K LS30K	LS37K LS45K LS55K	LS75K LS90K	LS110K LS132K LS160K	LS220K LS280K	LS375K LS450K
<b>PILOT DEVICES IN COVER</b>	"Start-Stop" push button.....(Twin Type)..... 1		KSS-2	\$35	\$35	\$35	\$35	\$35	\$35	\$35	\$35	\$35
	"Start-Stop" push button.....(Twin Type)..... 4, 12, 3R		KSS-3	90	90	90	90	90	90	90	90	90
	Extra Pushbutton..... 1		-	70	70	70	70	70	70	70	70	70
	"Up-Down-Stop" push button..... 1, 4, 12		UDS	160	160	160	160	160	160	160	160	160
	"Forward-Reverse-Stop" push button..... 1, 4, 12		FRS	160	160	160	160	160	160	160	160	160
	"Fast-Slow-Stop" push button..... 1, 4, 12		FSS	160	160	160	160	160	160	160	160	160
	"Start-Stop" push button and "Hand-Off-Auto" selector switch..... Any		SS-HOA	-	180	180	180	180	180	180	180	180
	"Hand-Off-Auto" selector switch..... 1		HOA	35	35	35	35	35	35	35	35	35
	"Hand-Off-Auto" selector switch..... 4, 12, 3R		HOA	90	90	90	90	90	90	90	90	90
	"Forward-Off-Reverse" selector switch..... 3R, 4X, 12		FOR	90	90	90	90	90	90	90	90	90
<b>FULL VOLTAGE CONTROLS</b>	"High-Off-Low" selector switch..... 3R, 4X, 12		HOL	90	90	90	90	90	90	90	90	90
	Pilot Light..... 1, 4, 12		PL	60	60	60	60	60	60	60	60	60
	"On-Off" selector switch..... 1		KSN-1	35	35	35	35	35	35	35	35	35
	"On-Off" selector switch..... 3R, 4, 12		KSN-3	90	90	90	90	90	90	90	90	90
	Control circuit transformer Standard capacity: With fused primary and secondary 60 Hz. or 50 Hz..... 1, 4, 12		FT ___ V	\$135	\$135	\$135	\$280	\$280	\$340	\$380	\$400	\$440
	<b>Auxiliaries reference as AEG Only</b>											
	EXTRA AUXILIARIES.....Maximum Allowable (# of Aux. Possible).....			4	4	4	9	9	9	9	9	9
	(# of Aux. Standard).....			1N.O. / 1N.C	1N.O. / 1N.C	1N.O. / 1N.C	2N.O. / 1N.C	2N.O. / 1N.C	2N.O. / 1N.C	2N.O. / 1N.C	2N.O. / 1N.C	2N.O. / 1N.C
	Add 2N.O / 2N.C. Aux..... Top Mount: Side Mount:		.22T .22S	\$17 \$22	\$17 \$22	\$17 \$22	\$17 \$22	\$17 NA	\$17 NA	\$17 NA	\$17 NA	\$17 NA
	<b>RELAY TIMERS</b>	Control relay (limited to one relay having maximum of 4 poles)-specify poles..... 1, 12		AR	-	204	204	204	204	320	360	360
arrangement, voltage and type required..... 4, 9			AR	-	312	312	312	312	424	472	472	472
Timing relay (limit of one- specify "On" or "Off" delay)..... 1, 12, 4			TR - 7	-	336	336	336	336	336	336	336	336
Phase Reverse Relay			TR - 24	-	336	336	336	336	336	336	336	336
			FRR	-	330	330	330	330	300	300	300	300
<b>METERS AND METERING</b>	Ammeter in cover (includes current transformer if necessary on Size 2 and up)-specify poles..... 1, 12		AM	-	204	204	204	204	320	360	360	360
	Ammeter and switch..... 1, 12		AMSW	-	312	312	312	312	424	472	472	472
	Elapsed time meter..... 1, 12		EM	-	336	336	336	336	336	336	336	336
	Voltmeter..... 1, 12		VM	-	440	440	440	440	440	440	440	440
	Voltmeter and switch..... 1, 12		VM SW	-	330	330	330	330	330	330	330	330

\* Applies for ALL EEC, TEC and RTEC Contactors and Starters.  
Above are factory installed suffixes.  
NA = Not Available.

Discount Schedule EC  
For TEC, EEC, ECX

Discount Schedule "ST"  
For XLS, LSK, SXLSK