


**Type LS05
MINI POWER RELAY
MINI CONTACTOR**



**Type LS07
MINI POWER RELAY
MINI CONTACTOR**



**Type XLS05
MINI STARTER**

MINI CONTACTORS STARTERS POWER RELAYS

POSITIVE GUIDED RELAYS & CONTACTORS

AEG COMPONENT
CONTROLS

SERIES LS07 SPECIFICATIONS

- ✓ **16 Amp Resistive (UL)**
AC-1 (16 AMP 600 Volt)
- ✓ **Mechanical Life Operations**
10,000,000
- ✓ **Maximum HP Ratings**
3 Phase
460 Volt 3HP CE

SERIES LS05 SPECIFICATIONS

- ✓ **15 Amp Inductive (UL)**
AC-1 (20 AMP 600 Volt)
- ✓ **Mechanical Life Operations**
AC 10,000,000
- ✓ **Maximum HP Ratings**
3 Phase
460 Volt 5HP

Connection Options LS07

- Pressure Wire Terminals
 - Spade (Plug-On)
 - PC Board (pin terminal)
- Low Coil Burden 1.2 Watt**

Internationally Accepted

- CE, UL, IEC, S +, BS, VDE, CSA

Overload Relay Type B05

- Ambient Temperature Compensated
- Three Pole Plug-on Separate Mount
- Differential Single Phasing Protection

Enclosures

- M1 - General Purpose
- M12 - Dust Tight
- 4X - Non Metal
- Water & Dust Tight



ELECTRICAL & ELECTRONIC
CONTROLS, INC.
3881 DANBURY ROAD
BREWSTER, NY 10509
845-278-5777 FAX 845-278-5444