



Three Phase 3 Pole 600V			Thermal Overload Relay Adjustment Range (AMPS)	Basic Catalog No.	OPEN -O	Outdoor Dust Tight Rain Tight -S4 (IP55)
Three Phase Horse Power						
208V	230V	460V				
			0.10 - 0.16A	MMP20-B	\$44	\$67
			0.16 - 0.25A	MMP20-C	\$44	\$67
			0.25 - 0.40A	MMP20-D	\$44	\$67
			0.40 - 0.63A	MMP20-E	\$44	\$67
			0.63 - 1.00A	MMP20-F	\$44	\$67
		3/4	1.00 - 1.60A	MMP20-G	\$44	\$67
1/2	1/2	1	1.60 - 2.50A	MMP20-H	\$44	\$67
3/4	3/4	2	2.50 - 4.00A	MMP20-I	\$44	\$67
1	1 1/2	3	4.00 - 6.30A	MMP20-K	\$44	\$67
2	3	5	6.00 - 10.0A	MMP20-L	\$44	\$67
3	3	10	9.00 - 14.0A	MMP20-M	\$44	\$67
5	5	10	13.0 - 18.0A	MMP20-N	\$44	\$67
5	7 1/2	15	17.0 - 23.0A	MMP20-O	\$44	\$67
7 1/2	7 1/2	15	20.0 - 25.0A	MMP20-P	\$44	\$67

IP55 = Protected against dust & low pressure jets of water.

### Single Phase 2 Pole 230 Volt

Single Phase Horse Power		Thermal Overload Relay Adjustment Range (AMPS)	Basic Catalog No.	OPEN -O	Outdoor Dust Tight Rain Tight -S4 (IP55)
115V	230V				
	1/6	1.60 - 2.50A	SMMP20-H	\$44	\$67
	1/3	2.50 - 4.00A	SMMP20-I	\$44	\$67
1/4	1/2	4.00 - 6.30A	SMMP20-K	\$44	\$67
1/2	1	6.00 - 10.0A	SMMP20-L	\$44	\$67
3/4	2	9.00 - 14.0A	SMMP20-M	\$44	\$67
1	3	13.0 - 18.0A	SMMP20-N	\$44	\$67
1 1/2	3	17.0 - 23.0A	SMMP20-O	\$44	\$67
2	3	20.0 - 25.0A	SMMP20-P	\$44	\$67

