



**LOW COST
WATER TIGHT
DUST TIGHT**

All control stations below, as standard, are **Round Design**. If square is desired, simply place a "S" at the end of the part number.
Example: B22-S4-101S (same list)

B22-S4-201-S \$63.00 List

Start-Stop Non Metal PVC (UL 4X)

DESCRIPTION

Type S4 Enclosures are Non Metal PVC fully gasketed against dust and hose pressure water tight. (International Rating: IP 66 and UL 4X)

Type S4X Enclosures are UL and CSA - Fiberglass Reinforced Polyester and are fully gasketed & hose pressure water tight.

Type M4/12 are cast metal and meet NEMA 12/4 standards. Series B22mm Operators are Metal Nema 4/12.

ELECTRICAL RATINGS

All buttons supplied are heavy duty oil dust tight, Type 4(water tight) and Type 12/13. Each is 600 Volt, 10 Amp UL, CSA,

Button Size: Part number example: B22S4-101	B22-S4 PVC		B22-S4X Polyester		B22-M 4/12 Cast Aluminum	
	B22-S4-	LIST	B22-S4X-	LIST	B22-M4/12	LIST
ONE BUTTON						
Start	-101	\$39.00	-101	\$106.00	-101	\$62.00
Stop	-102	39.00	-102	106.00	-102	62.00
Stop (Maintained Mushroom Button) (push pull)	-104	55.00	-104	122.00	-104	78.50
Stop (Maintained Mushroom Button) per EN 418	-114 -418	64.00	-114 -418	129.00	-114 -418	87.00
Stop (Momentary Mushroom Button)	-104MO	48.00	-104MO	113.00	-104MO	71.00
Jog	-105	39.00	-105	106.00	-105	62.00
Off-On (Selector Switch)	-106	46.00	-106	112.00	-106	68.00
Open-Close (Selector Switch)	-107	46.00	-107	112.00	-107	68.00
For-Rev. (Selector Switch)	-108	54.00	-108	119.00	-108	77.00
Hand-Off-Auto (Selector Switch)	-109	54.00	-109	119.00	-109	77.00
Man.-Auto (Selector Switch)	-110	54.00	-110	119.00	-110	77.00
Red Pilot Light: Resistor Type 240V 60Hz	-112	60.00	-112	127.00	-112	83.00
Red Pilot Light: Full Voltage Type						
120V AC or DC	-113	44.00	-113	111.00	-113	67.00
Enclosure Only with 7/8" Drilling	S4-405-M1	19.00	S4X-M1	86.00	BMD-G1	42.00
TWO BUTTON						
Start-Stop	-201	63.00	-201	127.00	-201	84.00
On-Off	-202	63.00	-202	127.00	-202	84.00
For-Rev.	-203	63.00	-203	127.00	-203	84.00
Up-Down	-204	63.00	-204	127.00	-204	84.00
Open-Close	-205	63.00	-205	127.00	-205	84.00
High-Low	-206	63.00	-206	127.00	-206	84.00
Red Pilot Light, 1 Button:						
120V	-208	70.00	-208	130.00	-208	94.00
240V	-209	88.00	-209	148.00	-209	94.00
Enclosure Only with 7/8" Drilling	S4-406-M2	24.00	S4X-M2	87.00	BMD-G2	47.00
THREE BUTTON						
Start-Jog-Stop	-301	102.00	-301	153.00	-301	106.00
Open-Close-Stop	-302	102.00	-302	153.00	-302	106.00
Up-Down-Stop	-303	102.00	-303	153.00	-303	106.00
For-Rev.-Stop	-304	102.00	-304	153.00	-304	106.00
High-Low-Stop	-305	102.00	-305	153.00	-305	106.00
Up-Down-Stop	-306	102.00	-306	153.00	-306	106.00
Red Pilot Light and 2 Buttons:						
(Start-Stop)						
120V AC or DC	-307	105.00	-307	156.00	-307	112.00
240V AC or DC	-308	123.00	-308	174.00	-308	112.00
Enclosure Only with 7/8" Drilling	S4-408-M3	33.00	S4X-M3	93.00	BMD-G3	57.00

CONTROL STATIONS

UL (4X) ENCLOSURES IP 66 (FIELD PB MOUNTING) WEATHERPROOF AND HOSEPROOF
Industrial enclosures Junction Boxes/Pushbuttons Enclosures/ Terminal Boxes/Controls Enclosures

UL 4X

ENCLOSURES ONLY (22mm) 7/8" Standard Drilling or Optional (30mm) 1^{13/64"}



S4-406-M2 Enclosure

# Holes xx	Scarlet S4 (PVC)			Fiberglass (4X)			Dimensions (Inches)			
	Cat. No.	List	H	W	D*	Catalog No.	List	H	W	D*
1	S4-405-M1	\$19.00	4.1	4.1	2.2					
1	S4-406-M1	23.00	4.9	3.2	2.6					
2	S4-406-M2	24.00	4.9	3.2	2.6	B22-S4X-M1	\$86.00	7	4	3
3	S4-408-M3	33.00	6.9	4.1	3.2	B22-S4X-M2	87.00	7	4	3
4	S4-410-M4	36.00	6.9	5.9	3.2	B22-S4X-M3	93.00	9	4	3
6	S4-410-M6	38.00	6.9	5.9	3.2	B22-S4X-M4	94.00	9	4	3
8	S4-414-M8	58.00	8.7	6.9	4.7	B22-S4X-M6	98.00	6	6	4
12	S4-372-M12	110.00	11.1	8.7	4.3	B22-S4X-M8	108.00	10	8	4
						B22-S4X-M12	112.00	10	8	4

* Above enclosures are drilled for (22mm) 7/8" operators. For drillings to be (30mm) 1^{13/64"} full size, change "M" to "S" in part number (same price). **Example: S4-405-S1 \$19.00 List**