



Type REEC 3 Phase Reversing Contactors

LIST PRICES

| Resistive AC-1 | Inductive AC-3 | Horse Power Ratings UL 3 Phase Motor | | OPEN | NEMA 1 General Purpose (metal) | NEMA4X Hose Dust Tight (non metal) | NEMA 4/12 (metal) | NEMA 3R Hose + Dust Tight Outdoor (metal) | Dimensions mm/inches open style | |
|-------------------|-------------------|--|-------|------------------------------|---|---|------------------------------|--|---------------------------------------|-----------|
| | | Volts | HP | | | | | | MM/Inches | |
| 25A | 12A | 200V | 3 | REEC 12 - * 0 \$90.00 | REEC 12 - * 1 \$173.00 | REEC 12 - * 4X \$205.00 | REEC 12 - * 4 \$230.00 | REEC 12 - * 3R \$229.00 | H | 74/2.91" |
| | | 230V | 3 | | | | | | W | 104/4.09" |
| | | 480V | 7 1/2 | | | | | | D(AC) | 80/3.15" |
| | | 600V | 10 | | | | | | D(DC) | 115/4.53" |
| 32A | 18A | 200V | 5 | REEC 18 - * 0 \$111.00 | REEC 18 - * 1 \$211.00 | REEC 18 - * 4X \$242.00 | REEC 18 - * 4 \$263.00 | REEC 18 - * 3R \$258.00 | H | 74/2.91" |
| | | 230V | 5 | | | | | | W | 106/4.17" |
| | | 480V | 10 | | | | | | D(AC) | 85/3.35" |
| | | 600V | 15 | | | | | | D(DC) | 120/4.72" |
| 40A | 25A | 200V | 5 | REEC 25 - * 0 \$132.00 | REEC 25 - * 1 \$237.00 | REEC 25 - * 4X \$276.00 | REEC 25 - * 4 \$284.00 | REEC 25 - * 3R \$279.00 | H | 84/3.30" |
| | | 230V | 7 1/2 | | | | | | W | 126/4.96" |
| | | 480V | 15 | | | | | | D(AC) | 93/3.66" |
| | | 600V | 20 | | | | | | D(DC) | 130/5.12" |
| 50A | 32A | 200V | 10 | REEC 32 - * 0 \$156.00 | REEC 32 - * 1 \$266.00 | REEC 32 - * 4X \$317.00 | REEC 32 - * 4 \$317.00 | REEC 32 - * 3R \$311.00 | H | 84/3.30" |
| | | 230V | 10 | | | | | | W | 126/4.96" |
| | | 480V | 20 | | | | | | D(AC) | 98/3.86" |
| | | 600V | 25 | | | | | | D(DC) | 135/5.31" |
| 60A | 40A | 200V | 10 | REEC 40 - * 0 \$227.00 | REEC 40 - * 1 \$375.00 | REEC 40 - * 4X \$423.00 | REEC 40 - * 4 \$407.00 | REEC 40 - * 3R \$391.00 | H | 127/5.00" |
| | | 230V | 10 | | | | | | W | 165/6.50" |
| | | 480V | 30 | | | | | | D(AC) | 114/4.49" |
| | | 600V | 30 | | | | | | D(DC) | 171/6.73" |

| *Coil Voltage Suffix | |
|---------------------------|---------------|
| * - Add Suffix AC Voltage | *- DC Voltage |
| -A = 120V 50/60Hz | |
| -C = 208V up to 230V 60Hz | -DCM = 12VDC |
| -E = 480V 60Hz, 400V 50Hz | -DCN = 24VDC |
| -F = 600V 60Hz | -DCO = 48VDC |
| -D = 380V 50Hz | -DCP = 125VDC |
| -G = 24V 50/60Hz | -DCR = 220VDC |
| -H = 277V(280) 60Hz | |
| -B = 220V 50/60Hz | |

Contact Factory for additional coil voltages not listed.
208V "c" Coil -5% Voltage Tolerance.

| DC Coil Price Adder Size + List Price |
|--|
| EEC 12-32 + \$60 |
| EEC 40-80 + \$120 |
| EEC 115 + No Adder |

