

Reversing Contactors (3 Phase)

AC - 1 Amps	AC - 3 Amps	Horse Power Rating 3 Phase		OPEN	NEMA 1 (METAL) Enclosed	NEMA 4X (NON-METAL) Enclosed -4X
		Volts	HP			
25A	9A	200V	3HP	RLS4K -*0	RLS4K -*1	RLS4K -*4X
		230V	3HP			
		460V	5HP			
		600V	7.5HP			
		LIST				
25A	12A	200V	3HP	RLS5K -*0	RLS5K -*1	RLS5K -*4X
		230V	3HP			
		460V	7.5HP			
		600V	10HP			
		LIST				
32A	18A	200V	5HP	RLS7K -*0	RLS7K -*1	RLS7K -*4X
		230V	5HP			
		460V	10HP			
		600V	15HP			
		LIST				
45A	25A	200V	5HP	RLS11K -*0	RLS11K -*1	RLS11K -*4X
		230V	7.5HP			
		460V	15HP			
		600V	15HP			
		LIST				
60A	32A	200V	10HP	RLS15K -*0	RLS15K -*1	RLS15K -*4X
		230V	10HP			
		460V	20HP			
		600V	25HP			
		LIST				
60A	40A	200V	10HP	RLS18K -*0	RLS18K -*1	RLS18K -*4X
		230V	10HP			
		460V	25HP			
		600V	25HP			
		LIST				
90A	50A	200V	15HP	RLS22K -*0	RLS22K -*1	RLS22K -*4X
		230V	15HP			
		460V	30HP			
		600V	40HP			
		LIST				
110A	65A	200V	20HP	RLS30K -*0	RLS30K -*1	RLS30K -*4X
		230V	20HP			
		460V	40HP			
		600V	50HP			
		LIST				
110A	80A	200V	20HP	RLS37K -*0	RLS37K -*1	RLS37K -*4X
		230V	25HP			
		460V	50HP			
		600V	60HP			
		LIST				

OPEN & ENCLOSED



RoHS Compliant



AC - 1 Amps	AC - 3 Amps	Horse Power Rating 3 Phase		OPEN	NEMA 1 (METAL) Enclosed	NEMA 4X (NON-METAL) Enclosed -4X
		Volts	HP			
140A	95A	200V	25HP	RLS45K -*0	RLS45K -*1	RLS45K -*4X
		230V	30HP			
		460V	60HP			
		600V	75HP			
		LIST				
140A	105A	200V	30HP	RLS55K -*0	RLS55K -*1	RLS55K -*4X
		230V	40HP			
		460V	75HP			
		600V	75HP			
		LIST				
250A	150A	200V	40HP	RLS75K -*0	RLS75K -*1	RLS75K -*4X
		230V	50HP			
		460V	100HP			
		600V	125HP			
		LIST				
250A	185A	200V	50HP	RLS90K -*0	RLS90K -*1	RLS90K -*4X
		230V	60HP			
		460V	125HP			
		600V	150HP			
		LIST				
315A	205A	200V	60HP	RLS110K -*0	RLS110K -*1	RLS110K -*4X
		230V	75HP			
		460V	150HP			
		600V	150HP			
		LIST				
315A	250A	200V	60HP	RLS132K -*0	RLS132K -*1	RLS132K -*4X
		230V	75HP			
		460V	150HP			
		600V	150HP			
		LIST				
450A	309A	200V	100HP	RLS160K -*0	RLS160K -*1	RLS160K -*4X
		230V	100HP			
		460V	250HP			
		600V	300HP			
		LIST				
600A	420A	200V	125HP	RLS220K -*0	RLS220K -*1	RLS220K -*4X
		230V	150HP			
		460V	300HP			
		600V	400HP			
		LIST				
700A	550A	200V	150HP	RLS280K -*0	RLS280K -*1	RLS280K -*4X
		230V	200HP			
		460V	400HP			
		600V	500HP			
		LIST				

*Coil Suffix Chart

FOR LS4K - LS18K FOR LS22K - LS55K

*AC 60Hz	50Hz	*AC 60Hz	50Hz	FOR LS75K - LS375K (3 Pole)
-G 24	24	-G 24	24	AC/DC 50/60 Hz + DC
-A 120	120	-A 120	120	-N 24-28V
-B 200	200	-B 200	200	-AP 110-127V
-C 220	220	-C 220	220	-CR 220-250V
-H 277	230	-H 277	230	-EX 440-500V
-E 480	380	-E 480	380	No additional Charge for DC LS75K - LS375K
-F 600	500	-F 600	500	
DC		DC		For Accessories
-MSW 12VDC		-NSW 24-28VDC		See Page 60,61
-NSW 24VDC		-OSW 42-48VDC		
-OSW 48VDC		-PSW 110-127VDC		
-PSW 110VDC		-RSW 220-250VDC		
-RSW 220VDC				
Add \$60 for DC		Add \$90 for DC		

Reversing Contactors are supplied wired. For units desired less wire Add **Suffix - LW** Contact Factory for deduction of price.

Enclosure Description

Nema 1 - General Purpose (indoor)
Nema 4X- Non - Metal (outdoor)
Dust tight / water tight.

Open Type

No Enclosure

To Order Reversing Contactor

Example: 5 HP 460V Reversing Contactor 120VAC Coil

Part # RLS4K-AO

List = \$183.00

Discount Schedule ST